

ADXXL73D29/2-24

ADVANTAGE GOLD II XXL 73D29



- Tapered body in HLE 420
- Double axle with parabolic leaves and rear free-steering axle
- Load-proportional air brakes
- Wheels 650/55R26.5
- Hydraulic door with grain chute
- Tipping by compressor
- French certification for 26 T

Standard equipment

- | | |
|--|---|
| <ul style="list-style-type: none"> ✓ Reinforced tapered monocoque body with upper body edge protection and reinforcing lengthwise fold (ST420 high tensile steel - 4 mm) ✓ Chassis made of 300 x 100 x 10 mm tubes ✓ 1-part hydraulic door (with seal and safety system with check valve) ✓ 500 x 500 mm multi-position central grain chute (with notches) ✓ Sight window on body (with perspex plate and galvanised protective grating) ✓ Galvanised access ladder ✓ Sprung drawbar ✓ Ø 50 mm bolted flat eyelet ✓ Hydraulic parking stand | <ul style="list-style-type: none"> ✓ Hose holder ✓ Dual-line air brakes ✓ Rear bumper ✓ LED flash light (flashing beacon on lighting) ✓ Road tandem with connecting rods (1,820 mm parabolic leaves) ✓ Tipping system with 1,000 rpm compressor (with hydraulic control) ✓ Pre-equipment for weight transfer ✓ Rear free-steering axle (DA) |
|--|---|

Specific equipment ADXXL73D29/2-24

- L-XXL2-73D29-24 GOLD2 XXL 7300D monocoque tipping trailer
- KHFR40-26 French national certification: 26 t maximum permissible axle load (+ 3/4 t at the eyelet) at 40 km/h for double-axle vehicle (cat. R)
- 3592 x 2 Wheels 650/55R26.5 (BKT) FL693M 169 D (Ø 1.389 x 645 mm, 7.890 kg per wheel at 40 km/h and 4 bar) instead of 400R22.5
- 3153 Air brakes with spring-brake actuator instead of standard parking brake (air brakes compulsory)
- 138 Braking power in proportion to the load on bogie or rocker beam with sprung drawbar (air brakes compulsory)
- 1526 LED side marker lights

	Total €	Discount %	NET
RETAIL	63.830 €
		TOTAL