



ADGO46S13/1-22

ADVANTAGE GOLIATH 46S13



- Narrow monocoque body
- Sprung drawbar
- Wheels 620/75R26
- · Hydraulic brakes
- Ø 900 mm vertical beaters with Hardox knives
- · Retractable hammers on wear rings
- · Hydraulic tensioning of the moving floor
- Guillotine door

Standard equipment

- Monocogue body with monoblock rounded side walls
- ✓ 2 vertical beaters with removable coupling and regular spirals (Ø 900 mm) with removable blades on wear rings (spiral thickness: 10
- √ Mm)
- √ Reversible and interchangeable HARDOX blades (10 mm thick)
- √ 1.000 rpm drive shaft beater rotation speed: 430 rpm
- √ Bolted rectangular slats of moving floor (80 x 40)
- Hydraulic tensioning of the moving floor with under-tension security and RE mode locking
- Moving floor drive by tractor hydraulics with proportional electric control at the flow regulator (LB300 control box - max. 2
- √ Functions on the control box)
- √ Reinforced reduction gearbox for single-speed moving floor
- √ Mechanically welded steel gearwheels
- √ Protected P.T.O. and drive shaft
- Homocinetic transmission (cam security)

- √ Free wheel on the spreading system
- Anti-projection front cover
- √ Protected lights folding automatically with moving floor drive
- √ Galvanized side boards
- √ Sealing flap at the front and on the spreading table
- √ LED flash bar connected on lighting
- √ Ladder (EN 690)
- √ Removable mudguard
- √ Hydraulic brakes
- √ Sprung drawbar
- √ Hydraulic stand
- √ Certification 2020

Specific equipment ADGO46S13/1-22

L-GO46S13 GOLIATH 46S13 muck spreader

• 3633 Wheels 620/75R26 (ALLIANCE) A360 167 A8 (Ø 1.590 x 625 mm, 5.450 kg per wheel at 40 km/h

and 3,2 bar) instead of 400R22.5

L932175 Guillotine door for 46S13 and 54S15

• L955033 Beater with spoon knives (1 knife on 2) instead of standard beater

	Total €	Discount %	NET
RETAIL	48 040 €		
		TOTAL	

V 03-03-2025