



ADHVS42S09/2-24

ADVANTAGE HVS 42S09



- Monocoque, monoblock body
- Wheels 620/75R26
- Full axle
- Hydraulic brakes
- Guillotine door
- Ø 820 mm beaters
- HARDOX blades
- Hydraulic installation

Standard equipment

- Monocoque, monoblock body with lengthwise fold
- √ Manufactured according to ÉN 690 standard
- ✓ Moving floor with 2 shipping chains (Ø 14 mm 25 t per link except on model 59S16 => Ø 16 mm - 32 t)
- ✓ Moving floor drive via tractor hydraulics, manual flow adjustment
- ✓ Reversible, interchangeable HARDOX blades (thickness: 8 mm)
- √ Moulded gearwheels
- √ Homocinetic P.T.O.-shaft with cam limiter
- √ Free wheel on the spreading system
- √ Reversing camera with 7" LCD colour screen
- ✓ Anti-projection front cover
- ✓ Protected lighting with manual folding on tubes with springs

- √ LED flash bar connected to lighting
- √ Galvanised side boards
- √ Sealing flap at the front and on the spreading table
- √ Dual-line air brakes
- Sprung drawbar
- √ Ø 50 mm bolted flat eyelet
- √ Hydraulic parking stand
- 2 vertical beaters with regular spirals (Ø 820 mm) with removable blades (spiral thickness: 10 mm in ST 420 reinforced steel)
- √ 1.000 rpm drive shaft beater rotation speed: 420 rpm
- ✓ Moving floor with 2 shipping chains (Ø 14 mm 25 T per link)
- √ Tubular slats of moving floor (70 x 35)

Specific equipment ADHVS42S09/2-24

L-HVS42S09-24 HVS 42S09 muck spreader

KHFR Machine subject to French national certification

• 3633 Wheels 620/75R26 (ALLIANCE) A360 167 A8 (Ø 1.590 x 625 mm, 5.450 kg per wheel at 40 km/h

and 3,2 bar) instead of 400R22.5

315 Hydraulic brakes instead of air brakes on single-axle model

• **L932015** Guillotine door from 37S08 to 51S12

• 5271 Independent industrial hydraulic installation (including hydraulic filter and Ferti-CONTROL 500)

3663 Extra cost for low flow electro-hydraulic functions (only available on muck spreaders and

DRAKKAR) - per function

	Total €	Discount %	NET
RETAIL	42 155 €		
		TOTAL	

V 27-01-2025