

ADHVS37S08/1-22

ADVANTAGE HVS 37S08



- Narrow monocoque body
- Sprung drawbar
- Wheels 18.4/15x30 14 PR
- Hydraulic brakes
- Ø 820 mm vertical beaters with Hardox knives

Standard equipment

- | | |
|---|---|
| <ul style="list-style-type: none"> ✓ Monocoque and monoblock body with a fold over the whole length ✓ Moving floor drive by tractor hydraulics, manual adjustment of the flow ✓ Reversible and interchangeable HARDOX blades (thickness: 8 mm) ✓ Moulded gearwheel ✓ Homocinetic P.T.O.-shaft with cam limiter ✓ Free wheel on the spreading system ✓ Anti-projection front cover ✓ Protected lighting with manual folding on tubes with springs ✓ LED flash bar connected on lighting ✓ Galvanized side boards | <ul style="list-style-type: none"> ✓ Sealing flap at the front and on the spreading table ✓ Ladder (EN 690) ✓ Hydraulic brakes with pre-equipment for air brakes ✓ Sprung drawbar ✓ Hydraulic stand ✓ Certification 2020 ✓ 2 vertical beaters with regular spirals (Ø 820 mm) with removable blades (spiral thickness: 10 mm in ST 420 reinforced steel) ✓ 1.000 rpm drive shaft - beater rotation speed: 420 rpm ✓ Moving floor with 2 shipping chains (Ø 12 mm - 18 T per link) ✓ Tubular slats of moving floor (60 x 30) |
|---|---|

Specific equipment ADHVS37S08/1-22

- L-HVS37S08 HVS 37S08 muck spreader
- 5502 Wheels 18.4/15x30 14 PR (ALLIANCE) A324 (Ø 1.550 x 467 mm, 4.260 kg per wheel at 40 km/h and 3,2 bar) instead of 400R22.5

	Total €	Discount %	NET
RETAIL	34.505 €
		TOTAL