

ADXXL58D22/4-24

ADVANTAGE GOLD II XXL 58D22



- Tapered body made of HLE420
- Bogie with parabolic leaves
- Air brakes
- Wheels 560/60R22.5
- Free steering axle
- Hydraulic door with grain chute
- European certification 30 km/h

Standard equipment

- | | |
|--|---|
| <ul style="list-style-type: none"> ✓ Reinforced tapered monocoque body with upper body edge protection and reinforcing lengthwise fold (ST420 high tensile steel - 4 mm) ✓ 1-part hydraulic door (with seal and safety system with check valve) ✓ 500 x 500 mm multi-position central grain chute (with notches) ✓ Sight window on body (with perspex plate and galvanised protective grating) ✓ Galvanised access ladder ✓ Sprung drawbar ✓ Ø 50 mm bolted flat eyelet ✓ Hydraulic parking stand ✓ Hose holder | <ul style="list-style-type: none"> ✓ Dual-line air brakes ✓ Rear bumper ✓ LED flash light (flashing beacon on lighting) ✓ Bogie with parabolic leaves (1,480 mm on 53D19 and 58D22 and 1,600 mm on 62D24) ✓ Tubular chassis: <ul style="list-style-type: none"> - 300 x 100 x 8 mm on 5300D, - 300 x 100 x 10 mm on 5800D and 6200D. ✓ Tipping system with direct connection to the tractor ✓ Pre-equipment for weight transfer |
|--|---|

Specific equipment ADXXL58D22/4-24

- L-XXL2-58D22-24 GOLD2 XXL 5800D monocoque tipping trailer
- **KHEU30-16** European certification for 15,5 T maximum permissible weight on the axles (+ 3 T on the eyelet) at 30 km/h for double-axle vehicle (cat. R)
- **074** Free steering axle with shock absorber(s) and hydraulic locking system (DA). WARNING: the free steering axle must be locked as soon as you reach 15 km/h.
- **2212 x 2** Wheels 560/60R22.5 (BKT) Flotation 630 Ultra 161 D (Ø 1.244 x 543 mm, 6.300 kg per wheel at 40 km/h and 4 bar) instead of 400R22.5
- **3153** Air brakes with spring-brake actuator instead of standard parking brake (air brakes compulsory)
- **1526** LED side marker lights

	Total €	Discount %	NET
RETAIL	43.540 €
TOTAL		