

ADGO54S15/5-24

ADVANTAGE GOLIATH 54S15

Non-contractual picture



- Monocoque body with monoblock rounded side walls
- Wheels 650/75R32
- Hydraulic brakes
- Guillotine door
- HARDOX blades
- Proportional flow with electronic management
- Hydraulic installation - FC 4000

Standard equipment

- | | |
|---|---|
| <ul style="list-style-type: none"> ✓ Monocoque body with monoblock rounded side walls ✓ 2 vertical beaters with removable coupling and regular spirals (Ø 900 mm) with removable blades on wear rings (spiral thickness: 10 Mm) ✓ Reversible and interchangeable HARDOX blades (10 mm thick) ✓ 1.000 rpm drive shaft - beater rotation speed: 430 rpm ✓ Bolted rectangular slats of moving floor (80 x 40) ✓ Hydraulic tensioning of the moving floor with under-tension security and RE mode locking ✓ Moving floor drive by tractor hydraulics with proportional electric control at the flow regulator (LB300 control box - max. 2 Functions on the control box) ✓ Reinforced reduction gearbox for single-speed moving floor ✓ Mechanically welded steel gearwheels ✓ Protected P.T.O. and drive shaft ✓ Homocinetic transmission (cam security) | <ul style="list-style-type: none"> ✓ Free wheel on the spreading system ✓ Anti-projection front cover ✓ Protected lights folding automatically with moving floor drive ✓ Galvanized side boards ✓ Sealing flap at the front and on the spreading table ✓ LED flash bar connected on lighting ✓ Ladder (EN 690) ✓ Removable mudguard ✓ Hydraulic brakes ✓ Sprung drawbar ✓ Hydraulic stand ✓ Certification 2020 ✓ Moving floor with 2 shipping chains (Ø 16 mm links - 32 t per link) |
|---|---|

Specific equipment ADGO54S15/5-24

- L-GO54S15-24 GOLIATH 54S15 muck spreader
- KHFR Machine subject to French national certification
- 5554 Wheels 650/75R32 (BKT) Agrimax RT600 DT43 172 A8 (Ø 1.785 x 645 mm, 6.300 kg per wheel at 40 km/h) instead of 400R22.5
- 315 Hydraulic brakes instead of air brakes on single-axle model
- L932175 Guillotine door for 46S13 and 54S15
- 5784 Beaters with spoon knives (1 knife on 2) instead of standard beaters
- 3666 Independent industrial hydraulic installation (including hydraulic filter and Ferti-CONTROL 4000)
- 3732 DPA on Ferti-CONTROL 4000 allowing the regulation of the floor speed according to the driving speed - including display of the driving speed (M/min). Allows also the regulation of the speed of the floor depending on the door opening (in combination with ref. 3116 to be taken additionally).
WARNING:
- on HORIZON model: ref. 3116 compulsory;
- Ferti-CONTROL 4000 compulsory.
- 3116 Electronic door opening indicator, spreader counter and moving floor starting safety (according to the door opening) - guillotine door compulsory)
- 3663 Extra cost for low flow electro-hydraulic functions (only available on muck spreaders and DRAKKAR) - per function

	Total €	Discount %	NET
RETAIL	62 705 €
TOTAL		