



ADHVS51S12/2-22

ADVANTAGE HVS 51S12



- Narrow monocoque body
- Sprung drawbar
- Wheels 620/75R26
- · Hydraulic brakes
- Ø 900 mm vertical beaters with Hardox knives
- Guillotine door
- · Hydraulic installation
- Ferti-CONTROL 300 control box

Standard equipment

- √ Monocoque and monoblock body with a fold over the whole length
- Moving floor drive by tractor hydraulics, manual adjustment of the flow
- √ Reversible and interchangeable HARDOX blades (thickness: 8 mm)
- ✓ Moulded gearwheel
- √ Homocinetic P.T.O.-shaft with cam limiter
- √ Free wheel on the spreading system
- Anti-projection front cover
- √ Protected lighting with manual folding on tubes with springs
- ✓ LED flash bar connected on lighting.
- Galvanized side boards
- Sealing flap at the front and on the spreading table

- Ladder (EN 690)
- √ Hydraulic brakes with pre-equipment for air brakes
- √ Sprung drawbar
- √ Hydraulic stand
- √ Certification 2020
- 2 vertical beaters with regular spirals (Ø 900 mm) with removable blades (spiral thickness: 10 mm in ST 420 reinforced steel)
- ✓ Interchangeable beater stand on wear ring
- √ 1.000 rpm drive shaft beater rotation speed: 430 rpm
- / Moving floor with 2 shipping chains (Ø 14 mm 25 T per link)
- Rectangular slats of moving floor (80 x 40)

Specific equipment ADHVS51S12/2-22

L-HVS51S12 HVS 51S12 muck spreader

• 3633 Wheels 620/75R26 (ALLIANCE) A360 167 A8 (Ø 1.590 x 625 mm, 5.450 kg per wheel at 40 km/h

and 3,2 bar) instead of 400R22.5

L932015 Guillotine door from 37S08 to 51S12

• L955033 Beater with spoon knives (1 knife on 2) instead of standard beater

L957006 Hydraulic installation with proportional electric control (including LB300 control box with reverse -

max. 2 functions on box)

L957011 Electric door control (take L957001 or L957006)

	Total €	Discount %	NET
RETAIL	50 935 €		
		TOTAL	

V 03-03-2025