

## ADHVS43S09/2-24

## ADVANTAGE HVS 43S09



- Narrow monocoque body
- Sprung drawbar
- Wheels 620/75R26
- Hydraulic brakes
- Ø 820 mm vertical beaters with Hardox knives
- Guillotine door
- Hydraulic installation
- Simplified DPA (proportional flow) on Ferti-CONTROL 500 control box

### Standard equipment

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>✓ Monocoque, monoblock body with lengthwise fold</li> <li>✓ Manufactured according to EN 690 standard</li> <li>✓ Moving floor with 2 shipping chains (Ø 14 mm - 25 t per link except on model 59S16 =&gt; Ø 16 mm - 32 t)</li> <li>✓ Moving floor drive via tractor hydraulics, manual flow adjustment</li> <li>✓ Reversible, interchangeable HARDOX blades (thickness: 8 mm)</li> <li>✓ Moulded gearwheels</li> <li>✓ Homocinetic P.T.O.-shaft with cam limiter</li> <li>✓ Free wheel on the spreading system</li> <li>✓ Reversing camera with 7" LCD colour screen</li> <li>✓ Anti-projection front cover</li> <li>✓ Protected lighting with manual folding on tubes with springs</li> </ul> | <ul style="list-style-type: none"> <li>✓ LED flash bar connected to lighting</li> <li>✓ Galvanised side boards</li> <li>✓ Sealing flap at the front and on the spreading table</li> <li>✓ Dual-line air brakes</li> <li>✓ Sprung drawbar</li> <li>✓ Ø 50 mm bolted flat eyelet</li> <li>✓ Hydraulic parking stand</li> <li>✓ 2 vertical beaters with regular spirals (Ø 820 mm) with removable blades (spiral thickness: 10 mm in ST 420 reinforced steel)</li> <li>✓ 1.000 rpm drive shaft - beater rotation speed: 420 rpm</li> <li>✓ Moving floor with 2 shipping chains (Ø 14 mm - 25 T per link)</li> <li>✓ Tubular slats of moving floor (80 x 40)</li> </ul> |
|---|---|

### Specific equipment ADHVS43S09/2-24

- L-HVS43S09-24 HVS 43S09 muck spreader
- KHFR Machine subject to French national certification
- 3633 Wheels 620/75R26 (ALLIANCE) A360 167 A8 (Ø 1.590 x 625 mm, 5.450 kg per wheel at 40 km/h and 3,2 bar) instead of 400R22.5
- 315 Hydraulic brakes instead of air brakes on single-axle model
- L932015 Guillotine door from 37S08 to 51S12
- 5784 Beaters with spoon knives (1 knife on 2) instead of standard beaters
- 5271 Independent industrial hydraulic installation (including hydraulic filter and Ferti-CONTROL 500)
- 5760 Simplified DPA (proportional flow) on Easy-CONTROL terminal instead of Ferti-Control 500 (ref. 5270 or 5271 compulsory)
- 3663 Extra cost for low flow electro-hydraulic functions (only available on muck spreaders and DRAKKAR) - per function

	Total €	Discount %	NET
<b>RETAIL</b>	50.477 €	.....	.....
<b>TOTAL</b>			.....