

ADHVS51S12/6-26

ADVANTAGE HVS 51S12

Non-contractual picture



- Narrow monocoque body
- Sprung drawbar
- Wheels 620/75R26
- Dual line hydraulic brakes
- Ø 900 mm vertical beaters with Hardox knives
- Guillotine door
- Hydraulic installation
- Electro-hydraulic controls with ISOBUS
- European certification for 30 km/h

Standard equipment

- ✓ Monocoque, monoblock body with lengthwise fold
- ✓ Manufactured according to EN 690 standard
- ✓ Moving floor with 2 shipping chains (Ø 14 mm - 25 t per link except on model 59S16 => Ø 16 mm - 32 t)
- ✓ Moving floor drive via tractor hydraulics, manual flow adjustment
- ✓ Reversible, interchangeable HARDOX blades (thickness: 8 mm)
- ✓ Moulded gearwheels
- ✓ Homocinetic P.T.O.-shaft with cam limiter
- ✓ Free wheel on the spreading system
- ✓ Reversing camera with 7" LCD colour screen
- ✓ Anti-projection front cover
- ✓ Protected lighting with manual folding on tubes with springs
- ✓ LED flash bar connected to lighting
- ✓ Galvanised side boards
- ✓ Sealing flap at the front and on the spreading table
- ✓ Dual-line air brakes
- ✓ Sprung drawbar
- ✓ Ø 50 mm bolted flat eyelet
- ✓ Hydraulic parking stand
- ✓ 2 vertical beaters with regular spirals (Ø 900 mm) with removable blades (spiral thickness: 10 mm in ST 420 reinforced steel)
- ✓ Interchangeable beater stand on wear ring
- ✓ 1.000 rpm drive shaft - beater rotation speed: 430 rpm
- ✓ Moving floor with 2 shipping chains (Ø 14 mm - 25 T per link)
- ✓ Rectangular slats of moving floor (80 x 40)

Specific equipment ADHVS51S12/6-26

- **L-HVS51S12-26** HVS 51S12 muck spreader
- **KHEU30-10S** European certification for 10 t maximum permissible axle load (+ 3 t at the eyelet) at 30 km/h for single-axle vehicle (cat. S)
- **3633** Wheels 620/75R26 (ALLIANCE) A360 167 A8 (Ø 1,590 x 625 mm, 5,450 kg per wheel at 40 km/h and 3.2 bar) instead of 400R22.5
- **1526** LED side marker lights
- **L932015** Guillotine door from 37S08 to 51S12
- **5784** Beaters with spoon knives (1 out of 2 knives) instead of standard beaters
- **5841** Autonomous industrial hydraulic installation (including ISOBUS "machine" components (ref. 5839))
- ATTENTION: compatible tractor terminal or JOSKIN terminal to be purchased separately.
- **3663** Extra cost for low-flow electro-hydraulic functions (only available on muck spreaders and DRAKKAR) - per function
- **5890** Dual-line hydraulic brakes (including manual corrector) on single-axle vehicle instead of air brakes
- **5840** Easy-CONTROL control box (with power cable) for controlling the main functions of an ISOBUS-equipped machine (ref. 5839 compulsory)

	Total £	Discount %	NET
RETAIL	50.108 £		
TOTAL			