

ADGO46S13/2-22

ADVANTAGE GOLIATH 46S13



- Monocoque body with monoblock rounded side walls
- HARDOX blades
- Removable blades on wear rings
- Hydraulic tensioning of the moving floor
- Hydraulic brakes
- Wheels 620/75R26
- Guillotine door
- Hydraulic installation

Standard equipment

- ✓ Monocoque body with monoblock rounded side walls
- ✓ 2 vertical beaters with removable coupling and regular spirals (Ø 900 mm) with removable blades on wear rings (spiral thickness: 10 Mm)
- ✓ Reversible and interchangeable HARDOX blades (10 mm thick)
- ✓ 1.000 rpm drive shaft - beater rotation speed: 430 rpm
- ✓ Bolted rectangular slats of moving floor (80 x 40)
- ✓ Hydraulic tensioning of the moving floor with under-tension security and RE mode locking
- ✓ Moving floor drive by tractor hydraulics with proportional electric control at the flow regulator (LB300 control box - max. 2 Functions on the control box)
- ✓ Reinforced reduction gearbox for single-speed moving floor
- ✓ Mechanically welded steel gearwheels
- ✓ Protected P.T.O. and drive shaft
- ✓ Homocinetic transmission (cam security)
- ✓ Free wheel on the spreading system
- ✓ Anti-projection front cover
- ✓ Protected lights folding automatically with moving floor drive
- ✓ Galvanized side boards
- ✓ Sealing flap at the front and on the spreading table
- ✓ LED flash bar connected on lighting
- ✓ Ladder (EN 690)
- ✓ Removable mudguard
- ✓ Hydraulic brakes
- ✓ Sprung drawbar
- ✓ Hydraulic stand
- ✓ Certification 2020

Specific equipment ADGO46S13/2-22

- **L-GO46S13** GOLIATH 46S13 muck spreader
- **3633** Wheels 620/75R26 (ALLIANCE) A360 167 A8 (Ø 1.590 x 625 mm, 5.450 kg per wheel at 40 km/h and 3,2 bar) instead of 400R22.5
- **L932175** Guillotine door for 46S13 and 54S15
- **L955033** Beater with spoon knives (1 knife on 2) instead of standard beater
- **L957032** Hydraulic installation with proportional electric control and with reverse
- **L957034** Electric door control (take L957032 or L957033)

	Total €	Discount %	NET
RETAIL	54 009 €
TOTAL		