

## ADGO54S15/6-24

## ADVANTAGE GOLIATH 54S15

Non-contractual picture



- **Narrow monocoque body**
- **Sprung drawbar**
- **Wheels 650/75R32**
- **Hydraulic brakes**
- **Ø 900 mm vertical beaters with Hardox knives**
- **Guillotine door**
- **Hydraulic installation**
- **Simplified DPA (proportional flow) on Ferti-CONTROL 500 control box**

### Standard equipment

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>✓ Monocoque body with monoblock rounded side walls</li> <li>✓ Manufactured according to EN 690 standard</li> <li>✓ 2 vertical beaters with removable coupling and balanced spirals (Ø 900 mm) with retractable hammers on wear rings (spiral thickness: 10 mm)</li> <li>✓ Reversible, interchangeable HARDOX blades (thickness: 10 mm)</li> <li>✓ 1,000-rpm drive shaft - beater rotation speed: 430 rpm</li> <li>✓ Bolted rectangular moving floor slats (80 x 40 mm)</li> <li>✓ Hydraulic tensioning of the moving floor with under-tension security and RE mode locking</li> <li>✓ Moving floor drive via tractor hydraulics, manual flow adjustment</li> <li>✓ Reinforced single-speed reduction gearbox of moving floor</li> <li>✓ Mechanically welded steel gearwheels</li> <li>✓ Protected P.T.O. and drive shaft</li> <li>✓ Homocinetic transmission (cam security)</li> </ul> | <ul style="list-style-type: none"> <li>✓ Free wheel on the spreading system</li> <li>✓ Reversing camera with 7" LCD colour screen</li> <li>✓ Anti-projection front cover</li> <li>✓ Galvanised side boards</li> <li>✓ Sealing flap at the front and on the spreading table</li> <li>✓ LED flash bar connected to lighting</li> <li>✓ Removable mudguards</li> <li>✓ Dual-line air brakes</li> <li>✓ Sprung drawbar</li> <li>✓ Ø 50 mm bolted flat eyelet</li> <li>✓ Hydraulic parking stand</li> <li>✓ Moving floor with 2 shipping chains (Ø 16 mm links - 32 t per link)</li> </ul> |
|---|---|

### Specific equipment ADGO54S15/6-24

- **L-GO54S15-24** GOLIATH 54S15 muck spreader
- **KHFR** Machine subject to French national certification
- **5554** Wheels 650/75R32 (BKT) Agrimax RT600 DT43 172 A8 (Ø 1.785 x 645 mm, 6.300 kg per wheel at 40 km/h) instead of 400R22.5
- **315** Hydraulic brakes instead of air brakes on single-axle model
- **L932175** Guillotine door for 46S13 and 54S15
- **5784** Beaters with spoon knives (1 knife on 2) instead of standard beaters
- **5271** Independent industrial hydraulic installation (including hydraulic filter and Ferti-CONTROL 500)
- **5760** Simplified DPA (proportional flow) on Ferti-Control 500 (ref. 5270 or 5271 compulsory)
- **3663** Extra cost for low flow electro-hydraulic functions (only available on muck spreaders and DRAKKAR) - per function

	Total €	Discount %	NET
<b>RETAIL</b>	59 240 €	.....	.....
<b>TOTAL</b>			.....