



## ADHVS51S12/3-24

## ADVANTAGE HVS 51S12



- Narrow monocogue body
- · Sprung drawbar
- Wheels 620/75R26
- Hydraulic brakes
- Ø 900 mm vertical beaters with Hardox knives
- Guillotine door
- Hydraulic installation
- Ferti-CONTROL 500 control box

## Standard equipment

- Monocogue and monoblock body with a fold over the whole length
- Moving floor drive by tractor hydraulics, manual adjustment of the flow
- Reversible and interchangeable HARDOX blades (thickness: 8 mm)
- Moulded gearwheel
- Homocinetic P.T.O.-shaft with cam limiter
- Free wheel on the spreading system
- Anti-projection front cover
- Protected lighting with manual folding on tubes with springs
- LED flash bar connected on lighting
- Galvanized side boards
- Sealing flap at the front and on the spreading table

- Ladder (EN 690)
- Hydraulic brakes with pre-equipment for air brakes
- Sprung drawbar
- Hydraulic stand
- Certification 2020
- 2 vertical beaters with regular spirals (Ø 900 mm) with removable blades (spiral thickness: 10 mm in ST 420 reinforced steel)
- Interchangeable beater stand on wear ring
- 1.000 rpm drive shaft beater rotation speed: 430 rpm
- Moving floor with 2 shipping chains (Ø 14 mm 25 T per link) Rectangular slats of moving floor (80 x 40)

## Specific equipment ADHVS51S12/3-24

L-HVS51S12-24 HVS 51S12 muck spreader

**KHFR** Machine subject to French national certification

3633 Wheels 620/75R26 (ALLIANCE) A360 167 A8 (Ø 1.590 x 625 mm, 5.450 kg per wheel at 40 km/h

and 3,2 bar) instead of 400R22.5

Hydraulic brakes instead of air brakes on single-axle model 315

L932015 Guillotine door from 37S08 to 51S12

Beaters with spoon knives (1 knife on 2) instead of standard beaters 5784

5271 Independent industrial hydraulic installation (including hydraulic filter and Ferti-CONTROL 500) Extra cost for low flow electro-hydraulic functions (only available on muck spreaders and

3663

DRAKKAR) - per function

	Total €	Discount %	NET
RETAIL	50 480 €		
		TOTAL	

V 03-03-2025