

ADGO54S15/7-26

ADVANTAGE GOLIATH 54S15



- Narrow monocoque body
- Sprung drawbar
- Wheels 650/75R32
- Dual line hydraulic brakes
- Ø 900 mm vertical beaters with Hardox knives
- Guillotine door
- Hydraulic installation
- Electro-hydraulic controls with ISOBUS
- European certification for 30 km/h

Standard equipment

- | | |
|---|---|
| ✓ Monocoque body with monoblock rounded side walls | ✓ Free wheel on the spreading system |
| ✓ Manufactured according to EN 690 standard | ✓ Reversing camera with 7" LCD colour screen |
| ✓ 2 vertical beaters with removable coupling and balanced spirals (Ø 900 mm) with retractable hammers on wear rings (spiral thickness: 10 mm) | ✓ Anti-projection front cover |
| ✓ Reversible, interchangeable HARDOX blades (thickness: 10 mm) | ✓ Galvanised side boards |
| ✓ 1,000-rpm drive shaft - beater rotation speed: 430 rpm | ✓ Sealing flap at the front and on the spreading table |
| ✓ Bolted rectangular moving floor slats (80 x 40 mm) | ✓ LED flash bar connected to lighting |
| ✓ Hydraulic tensioning of the moving floor with under-tension security and RE mode locking | ✓ Removable mudguards |
| ✓ Moving floor drive via tractor hydraulics, manual flow adjustment | ✓ Dual-line air brakes |
| ✓ Reinforced single-speed reduction gearbox of moving floor | ✓ Sprung drawbar |
| ✓ Mechanically welded steel gearwheels | ✓ Ø 50 mm bolted flat eyelet |
| ✓ Protected P.T.O. and drive shaft | ✓ Hydraulic parking stand |
| ✓ Homocinetic transmission (cam security) | ✓ Moving floor with 2 shipping chains (Ø 16 mm links - 32 t per link) |

Specific equipment ADGO54S15/7-26

- L-GO54S15-26 GOLIATH 54S15 muck spreader
- 5890 Dual-line hydraulic brakes (including manual corrector) on single-axle vehicle instead of air brakes
- KHEU30-10S European certification for 10 t maximum permissible axle load (+ 3 t at the eyelet) at 30 km/h for single-axle vehicle (cat. S)
- 5554 Wheels 650/75R32 (BKT) Agrimax RT600 DT43 172 A8 (Ø 1,785 x 645 mm, 6,300 kg per wheel at 40 km/h) instead of 400R22.5
- 1526 LED side marker lights
- L932175 Guillotine door for 46S13 and 54S15
- 5784 Beaters with spoon knives (1 out of 2 knives) instead of standard beaters
- 5841 Autonomous industrial hydraulic installation (including ISOBUS "machine" components (ref. 5839))
- ATTENTION: compatible tractor terminal or JOSKIN terminal to be purchased separately.
- 3663 Extra cost for low-flow electro-hydraulic functions (only available on muck spreaders and DRAKKAR) - per function
- 5840 Easy-CONTROL control box (with power cable) for controlling the main functions of an ISOBUS-equipped machine (ref. 5839 compulsory)

	Total £	Discount %	NET
RETAIL	57.338 £		



ADGO54S15/7-26

ADVANTAGE GOLIATH 54S15

	TOTAL	
--	-------	-------