

## ADXXL73D29/2-24

## ADVANTAGE GOLD II XXL 73D29



- Tapered body in HLE 420
- Double axle with parabolic leaves and rear free-steering axle
- Load-proportional air brakes
- Wheels 650/55R26.5
- Hydraulic door with grain chute
- Tipping by compressor
- French certification for 26 T

### Standard equipment

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>✓ Reinforced tapered monocoque body with upper body edge protection and reinforcing lengthwise fold (ST420 high tensile steel - 4 mm)</li> <li>✓ Chassis made of 300 x 100 x 10 mm tubes</li> <li>✓ 1-part hydraulic door (with seal and safety system with check valve)</li> <li>✓ 500 x 500 mm multi-position central grain chute (with notches)</li> <li>✓ Sight window on body (with perspex plate and galvanised protective grating)</li> <li>✓ Galvanised access ladder</li> <li>✓ Sprung drawbar</li> <li>✓ Ø 50 mm bolted flat eyelet</li> <li>✓ Hydraulic parking stand</li> </ul> | <ul style="list-style-type: none"> <li>✓ Hose holder</li> <li>✓ Dual-line air brakes</li> <li>✓ Rear bumper</li> <li>✓ LED flash light (flashing beacon on lighting)</li> <li>✓ Road tandem with rods (parabolic leaves)</li> <li>✓ Tipping system with 1,000 rpm compressor (with hydraulic control)</li> <li>✓ Pre-equipment for weight transfer</li> <li>✓ Rear free-steering axle (DA)</li> </ul> |
|--|---|

### Specific equipment ADXXL73D29/2-24

- L-XXL2-73D29-24 GOLD2 XXL 73D29 monocoque tipping trailer
- KHFR40-26 French national certification: 26 t maximum permissible axle load (+ 3/4 t at the eyelet) at 40 km/h for double-axle vehicle (cat. R)
- 3592 x 2 Wheels 650/55R26.5 (BKT) FL693M 169 D (Ø 1.389 x 645 mm, 7.890 kg per wheel at 40 km/h and 4 bar) instead of 400R22.5
- 3153 Air brakes with spring-brake actuator instead of standard parking brake (air brakes compulsory)
- 138 Braking power in proportion to the load on bogie or rocker beam with sprung drawbar (air brakes compulsory)
- 1526 LED side marker lights

	Total €	Discount %	NET
<b>RETAIL</b>	63 059 €	.....	.....
		<b>TOTAL</b>	.....