

ADXXL58D22/5-24

ADVANTAGE GOLD II XXL 58D22

Non-contractual picture



- Tapered body made of HLE420
- Bogie with parabolic leaves
- Air brakes
- Wheels 560/60R22.5
- Hydraulic door with grain chute
- European certification 30 km/h

Standard equipment

- ✓ Reinforced tapered monocoque body with upper body edge protection and reinforcing lengthwise fold (ST420 high tensile steel - 4 mm)
- ✓ 1-part hydraulic door (with seal and safety system with check valve)
- ✓ 500 x 500 mm multi-position central grain chute (with notches)
- ✓ Sight window on body (with perspex plate and galvanised protective grating)
- ✓ Galvanised access ladder
- ✓ Sprung drawbar
- ✓ Ø 50 mm bolted flat eyelet
- ✓ Hydraulic parking stand
- ✓ Hose holder
- ✓ Dual-line air brakes
- ✓ Rear bumper
- ✓ LED flash light (flashing beacon on lighting)
- ✓ Bogie with parabolic leaves
- ✓ Tubular chassis:
 - 300 x 100 x 8 mm on 53D19,
 - 300 x 100 x 10 mm on 58D22 and 62D24.
- ✓ Tipping system with direct connection to the tractor
- ✓ Pre-equipment for weight transfer

Specific equipment ADXXL58D22/5-24

- L-XXL2-58D22-24 GOLD2 XXL 58D22 monocoque tipping trailer
- KHEU30-16 European certification for 15,5 T maximum permissible weight on the axles (+ 3 T on the eyelet) at 30 km/h for double-axle vehicle (cat. R)
- 2212 x 2 Wheels 560/60R22.5 (BKT) Flotation 630 Ultra 161 D (Ø 1.244 x 543 mm, 6.300 kg per wheel at 40 km/h and 4 bar) instead of 400R22.5
- 3153 Air brakes with spring-brake actuator instead of standard parking brake (air brakes compulsory)
- 1526 LED side marker lights

	Total €	Discount %	NET
RETAIL	38 664 €
TOTAL		