

ADXXL8500T/1-26

ADVANTAGE GOLD II XXL 8500T



- Tapered body in HLE 420
- Tridem with parabolic leaves
- Double self-steering axle
- Air braking system in proportion to the load
- Wheels 600/55R26.5
- Hydraulic door with grain chute
- Tipping by compressor
- European certification for 40 km/h

Standard equipment

- ✓ Reinforced tapered monocoque body with upper body edge protection and reinforcing lengthwise fold (ST420 high tensile steel - 4 mm)
- ✓ Chassis made of 300 x 100 x 10 mm tube
- ✓ 1-part hydraulic door (with seal and anti-fall system with check valve)
- ✓ 500 x 500 mm multi-position central grain chute (with notches)
- ✓ Sight window on body (with perspex plate and galvanised protective grating)
- ✓ Galvanised access ladder
- ✓ Pre-equipment for front platform
- ✓ Sprung drawbar
- ✓ Ø 50 mm bolted flat eyelet
- ✓ Hydraulic parking stand
- ✓ Hose holder
- ✓ Dual-line air brakes
- ✓ Rear bumper
- ✓ LED flashing light (flashing beacon on lighting)
- ✓ Road tridem with connecting rods (parabolic leaves of 1,550 mm)
- ✓ Tipping system with 1,000 rpm compressor (with hydraulic control)
- ✓ Rear free-steering axle (DA)

Specific equipment ADXXL8500T/1-26

- L-XXL2-85T32-26 GOLD2 XXL 8500T monocoque tipping trailer
- KHEU40-27 European certification for 27 t maximum permissible axle load (+ 3/4 t at the eyelet) at 40 km/h for triple-axle vehicle (cat. R)
- 5781 Front self-steering axle instead of fixed axle on triple-axle vehicle
- 5782 Rear self-steering axle instead of free-steering axle on triple-axle vehicle
- 3785 x 3 Wheels 600/55R26.5 (BKT) FL630 Super 165 D (Ø 1,333 x 611 mm, 7,005 kg per wheel at 40 km/h and 4 bar) instead of 400R22.5
- 3153 Air brakes with spring cylinders instead of standard parking brake (air brakes compulsory)
- 138 Brakes in proportion to the load on mechanical suspension (air brakes compulsory)
- 1448 LED end outline marker lamps and side marker lights
- 935 2 rear LED work lights (with control via in-cab box or ISOBUS button (ISOBUS configuration required))
- 2408 Drawbar with large plate instead of small plate - including JOSKIN Ø 80 mm 4 t knee-joint eyelet (incompatible with fixed drawbar)

	Total €	Discount %	NET
RETAIL	83.145 €		
TOTAL			