

ADGO54S15/3-22

ADVANTAGE GOLIATH 54S15

Non-contractual picture



- **Narrow monocoque body**
- **Sprung drawbar**
- **Wheels 650/75R32**
- **Air brakes**
- **Ø 900 mm vertical beaters with Hardox knives**
- **Guillotine door**
- **Simplified DPA (proportional flow) on Ferti-CONTROL 500 control box**
- **European certification for 30 km/h**

Standard equipment

- | | |
|---|---|
| <ul style="list-style-type: none"> ✓ Monocoque body with monoblock rounded side walls ✓ 2 vertical beaters with removable coupling and regular spirals (Ø 900 mm) with removable blades on wear rings (spiral thickness: 10 mm) ✓ Reversible and interchangeable HARDOX blades (10 mm thick) ✓ 1.000 rpm drive shaft - beater rotation speed: 430 rpm ✓ Bolted rectangular slats of moving floor (80 x 40) ✓ Hydraulic tensioning of the moving floor with under-tension security and RE mode locking ✓ Moving floor drive by tractor hydraulics with proportional electric control at the flow regulator (LB300 control box - max. 2 functions on the control box) ✓ Reinforced reduction gearbox for single-speed moving floor ✓ Mechanically welded steel gearwheels ✓ Protected P.T.O. and drive shaft ✓ Homocinetic transmission (cam security) ✓ Free wheel on the spreading system | <ul style="list-style-type: none"> ✓ Anti-projection front cover ✓ Protected lights folding automatically with moving floor drive ✓ Galvanized side boards ✓ Sealing flap at the front and on the spreading table ✓ LED flash bar connected on lighting ✓ Ladder (EN 690) ✓ Removable mudguard ✓ Hydraulic brakes ✓ Sprung drawbar ✓ Hydraulic stand ✓ Certification 2020 ✓ Moving floor with 2 shipping chains (Ø 16 mm links - 32 t per link) |
|---|---|

Specific equipment ADGO54S15/3-22

- **L-GO54S15** GOLIATH 54S15 muck spreader
- **5554** Wheels 650/75R32 (BKT) Agrimax RT600 DT43 172 A8 (Ø 1.785 x 645 mm, 6.300 kg per wheel at 40 km/h) instead of 400R22.5
- **L97073** Air brakes instead of hydraulic brakes on single-axle vehicle
- **L971526** Side marker lights (compulsory in Belgium)
- **L932175** Guillotine door for 46S13 and 54S15
- **L955033** Beater with spoon knives (1 knife on 2) instead of standard beater
- **L956254** Ferti-CONTROL 500 alu control box with simplified DPA (proportional flow) - including electric moving floor drive control with flow regulator, moving floor on/off switch, simplified DPA, electric reverser and entry block for electrohydraulic functions (ref. 3663 compulsory per extra electrohydraulic function)
- **L957034** Electric door control (take L957032 or L957033)
- **KHEU30-10S** European certification for 10 T maximum permissible weight on the axle (+ 3 T on the eyelet) at 30 km/h for single-axle vehicle (cat. S)
- **3153** Air brakes with spring-brake actuator instead of standard parking brake (air brakes compulsory)

| | Total € | Discount % | NET |
|---------------|----------|------------|-------|
| RETAIL | 61.735 € | | |
| TOTAL | | | |