

ADXXL85T32/6-24

ADVANTAGE GOLD II XXL 85T32

Non-contractual picture



- Tapered body in HLE 420
- Tridem with parabolic leaves and front and rear free-steering axles
- Air braking system in proportion to the load
- Wheels 600/55R26.5
- Hydraulic door with grain chute
- Tipping by compressor
- European certification for 40 km/h

Standard equipment

- ✓ Reinforced tapered monocoque body with upper body edge protection and reinforcing lengthwise fold (ST420 high tensile steel - 4 mm)
- ✓ Chassis made of 300 x 100 x 10 mm tubes
- ✓ 1-part hydraulic door (with seal and safety system with check valve)
- ✓ 500 x 500 mm multi-position central grain chute (with notches)
- ✓ Sight window on body (with perspex plate and galvanised protective grating)
- ✓ Galvanised access ladder
- ✓ Sprung drawbar
- ✓ Ø 50 mm bolted flat eyelet
- ✓ Hydraulic parking stand
- ✓ Hose holder
- ✓ Dual-line air brakes
- ✓ Rear bumper
- ✓ LED flash light (flashing beacon on lighting)
- ✓ Road tridem with connecting rods (parabolic leaves of 1,550 mm)
- ✓ Tipping system with 1,000 rpm compressor (with hydraulic control)
- ✓ Rear free-steering axle (DA)

Specific equipment ADXXL85T32/6-24

- L-XXL2-85T32-24 GOLD2 XXL 8500T monocoque tipping trailer
- KHEU40-27 European certification for 27 T maximum permissible weight on the axles (+ 3 / 4 T on the eyelet) at 40 km/h for triple-axle vehicle (cat. R)
- 5780 Front free-steering axle instead of fixed axle on tridem
- 3785 x 3 Wheels 600/55R26.5 (BKT) FL630 Super 165 D (Ø 1.333 x 611 mm, 7.005 kg per wheel at 40 km/h and 4 bar) instead of 400R22.5
- 3153 Air brakes with spring-brake actuator instead of standard parking brake (air brakes compulsory)
- 138 Braking power in proportion to the load on bogie or rocker beam with sprung drawbar (air brakes compulsory)
- 1448 LED end outline marker lamps and side marker lights

	Total €	Discount %	NET
RETAIL	77.485 €
TOTAL		