

## ADHVS42S09/1-22

## ADVANTAGE HVS 42S09



- Narrow monocoque body
- Sprung drawbar
- Wheels 23.1x26
- Hydraulic brakes
- Ø 820 mm vertical beaters with Hardox knives
- Guillotine door
- Hydraulic installation

### Standard equipment

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>✓ Monocoque and monoblock body with a fold over the whole length</li> <li>✓ Moving floor drive by tractor hydraulics, manual adjustment of the flow</li> <li>✓ Reversible and interchangeable HARDOX blades (thickness: 8 mm)</li> <li>✓ Moulded gearwheel</li> <li>✓ Homocinetic P.T.O.-shaft with cam limiter</li> <li>✓ Free wheel on the spreading system</li> <li>✓ Anti-projection front cover</li> <li>✓ Protected lighting with manual folding on tubes with springs</li> <li>✓ LED flash bar connected on lighting</li> <li>✓ Galvanized side boards</li> </ul> | <ul style="list-style-type: none"> <li>✓ Sealing flap at the front and on the spreading table</li> <li>✓ Ladder (EN 690)</li> <li>✓ Hydraulic brakes with pre-equipment for air brakes</li> <li>✓ Sprung drawbar</li> <li>✓ Hydraulic stand</li> <li>✓ Certification 2020</li> <li>✓ 2 vertical beaters with regular spirals (Ø 820 mm) with removable blades (spiral thickness: 10 mm in ST 420 reinforced steel)</li> <li>✓ 1.000 rpm drive shaft - beater rotation speed: 420 rpm</li> <li>✓ Moving floor with 2 shipping chains (Ø 14 mm - 25 T per link)</li> <li>✓ Tubular slats of moving floor (70 x 35)</li> </ul> |
|---|---|

### Specific equipment ADHVS42S09/1-22

- **L-HVS42S09** HVS 42S09 muck spreader
- **1995** Wheels 23.1x26 14 PR (ALLIANCE) A347 156 A8 (Ø 1.605 x 587 mm, 4.800 kg per wheel at 40 km/h and 2,4 bar) instead of 400R22.5
- **L932015** Guillotine door from 37S08 to 51S12
- **L957006** Hydraulic installation with proportional electric control (including LB300 control box with reverse - max. 2 functions on box)
- **L957011** Electric door control (take L957001 or L957006)

	Total €	Discount %	NET
<b>RETAIL</b>	40 995 €	.....	.....
		<b>TOTAL</b>	.....