

ADXXL58D22/4-24

ADVANTAGE GOLD II XXL 58D22



- Tapered body made of HLE420
- Bogie with parabolic leaves
- Air brakes
- Wheels 560/60R22.5
- Free steering axle
- Hydraulic door with grain chute
- European certification 30 km/h

Standard equipment

- | | |
|---|--|
| ✓ Reinforced tapered monocoque body with upper body edge protection and reinforcing lengthwise fold (ST420 high tensile steel - 4 mm) | ✓ Dual-line air brakes |
| ✓ 1-part hydraulic door (with seal and safety system with check valve) | ✓ Rear bumper |
| ✓ 500 x 500 mm multi-position central grain chute (with notches) | ✓ LED flash light (flashing beacon on lighting) |
| ✓ Sight window on body (with perspex plate and galvanised protective grating) | ✓ Bogie with parabolic leaves |
| ✓ Galvanised access ladder | ✓ Tubular chassis: |
| ✓ Sprung drawbar | - 300 x 100 x 8 mm on 53D19, |
| ✓ Ø 50 mm bolted flat eyelet | - 300 x 100 x 10 mm on 58D22 and 62D24. |
| ✓ Hydraulic parking stand | ✓ Tipping system with direct connection to the tractor |
| ✓ Hose holder | ✓ Pre-equipment for weight transfer |

Specific equipment ADXXL58D22/4-24

- L-XXL2-58D22-24 GOLD2 XXL 58D22 monocoque tipping trailer
- KHEU30-16 European certification for 15,5 T maximum permissible weight on the axles (+ 3 T on the eyelet) at 30 km/h for double-axle vehicle (cat. R)
- 074 Free steering axle with shock absorber(s) and hydraulic locking system (DA). WARNING: the free steering axle must be locked as soon as you reach 15 km/h.
- 2212 x 2 Wheels 560/60R22.5 (BKT) Flotation 630 Ultra 161 D (Ø 1.244 x 543 mm, 6.300 kg per wheel at 40 km/h and 4 bar) instead of 400R22.5
- 3153 Air brakes with spring-brake actuator instead of standard parking brake (air brakes compulsory)
- 1526 LED side marker lights

	Total €	Discount %	NET
RETAIL	42 684 €		
TOTAL			