

ADHVS42S09/1-22

ADVANTAGE HVS 42S09



- Narrow monocoque body
- Sprung drawbar
- Wheels 23.1x26
- Hydraulic brakes
- Ø 820 mm vertical beaters with Hardox knives
- Guillotine door
- Hydraulic installation

Standard equipment

- | | |
|---|---|
| <ul style="list-style-type: none"> ✓ Monocoque and monoblock body with a fold over the whole length ✓ Moving floor drive by tractor hydraulics, manual adjustment of the flow ✓ Reversible and interchangeable HARDOX blades (thickness: 8 mm) ✓ Moulded gearwheel ✓ Homocinetic P.T.O.-shaft with cam limiter ✓ Free wheel on the spreading system ✓ Anti-projection front cover ✓ Protected lighting with manual folding on tubes with springs ✓ LED flash bar connected on lighting ✓ Galvanized side boards | <ul style="list-style-type: none"> ✓ Sealing flap at the front and on the spreading table ✓ Ladder (EN 690) ✓ Hydraulic brakes with pre-equipment for air brakes ✓ Sprung drawbar ✓ Hydraulic stand ✓ Certification 2020 ✓ 2 vertical beaters with regular spirals (Ø 820 mm) with removable blades (spiral thickness: 10 mm in ST 420 reinforced steel) ✓ 1.000 rpm drive shaft - beater rotation speed: 420 rpm ✓ Moving floor with 2 shipping chains (Ø 14 mm - 25 T per link) ✓ Tubular slats of moving floor (80 x 40) |
|---|---|

Specific equipment ADHVS42S09/1-22

- L-HVS42S09 HVS 42S09 muck spreader
- 1995 Wheels 23.1x26 14 PR (ALLIANCE) A347 156 A8 (Ø 1.605 x 587 mm, 4.800 kg per wheel at 40 km/h and 2,4 bar) instead of 400R22.5
- L932015 Guillotine door from 37S08 to 51S12
- L957006 Hydraulic installation with proportional electric control (including LB300 control box with reverse - max. 2 functions on box)
- L957011 Electric door control (take L957001 or L957006)

	Total €	Discount %	NET
RETAIL	41.665 €
	TOTAL	