

## ADGO54S15/4-22

## ADVANTAGE GOLIATH 54S15

Non-contractual picture



- **Narrow monocoque body**
- **Sprung drawbar**
- **Wheels 650/75R32**
- **Air brakes**
- **Ø 900 mm vertical beaters with Hardox knives**
- **Guillotine door**
- **Hydraulic installation**
- **Simplified DPA (proportional flow) on Ferti-CONTROL 500 control box**
- **European certification for 30 km/h**

### Standard equipment

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>✓ Monocoque body with monoblock rounded side walls</li> <li>✓ 2 vertical beaters with removable coupling and regular spirals (Ø 900 mm) with removable blades on wear rings (spiral thickness: 10 mm)</li> <li>✓ Reversible and interchangeable HARDOX blades (10 mm thick)</li> <li>✓ 1.000 rpm drive shaft - beater rotation speed: 430 rpm</li> <li>✓ Bolted rectangular slats of moving floor (80 x 40)</li> <li>✓ Hydraulic tensioning of the moving floor with under-tension security and RE mode locking</li> <li>✓ Moving floor drive by tractor hydraulics with proportional electric control at the flow regulator (LB300 control box - max. 2 functions on the control box)</li> <li>✓ Reinforced reduction gearbox for single-speed moving floor</li> <li>✓ Mechanically welded steel gearwheels</li> <li>✓ Protected P.T.O. and drive shaft</li> <li>✓ Homocinetic transmission (cam security)</li> <li>✓ Free wheel on the spreading system</li> </ul> | <ul style="list-style-type: none"> <li>✓ Anti-projection front cover</li> <li>✓ Protected lights folding automatically with moving floor drive</li> <li>✓ Galvanized side boards</li> <li>✓ Sealing flap at the front and on the spreading table</li> <li>✓ LED flash bar connected on lighting</li> <li>✓ Ladder (EN 690)</li> <li>✓ Removable mudguard</li> <li>✓ Hydraulic brakes</li> <li>✓ Sprung drawbar</li> <li>✓ Hydraulic stand</li> <li>✓ Certification 2020</li> <li>✓ Moving floor with 2 shipping chains (Ø 16 mm links - 32 t per link)</li> </ul> |
|---|---|

### Specific equipment ADGO54S15/4-22

- **L-GO54S15** GOLIATH 54S15 muck spreader
- **5554** Wheels 650/75R32 (BKT) Agrimax RT600 DT43 172 A8 (Ø 1.785 x 645 mm, 6.300 kg per wheel at 40 km/h) instead of 400R22.5
- **L97073** Air brakes instead of hydraulic brakes on single-axle vehicle
- **L971526** Side marker lights (compulsory in Belgium)
- **L932175** Guillotine door for 46S13 and 54S15
- **L955033** Beater with spoon knives (1 knife on 2) instead of standard beater
- **L956255** Ferti-CONTROL 500 alu control box with simplified DPA (proportional flow) on hydraulic installation instead of LB300 - including electric moving floor drive control with flow regulator, moving floor on/off switch, simplified DPA, electric reverser and entry block for electrohydraulic functions (ref. 3663 compulsory per additional electrohydraulic function, ref. L957006 compulsory).
- **L957032** Hydraulic installation with proportional electric control and with reverse
- **L957034** Electric door control (take L957032 or L957033)
- **3153** Air brakes with spring-brake actuator instead of standard parking brake (air brakes compulsory)
- **KHEU30-10S** European certification for 10 T maximum permissible weight on the axle (+ 3 T on the eyelet) at 30 km/h for single-axle vehicle (cat. S)

	Total €	Discount %	NET
<b>RETAIL</b>	65.300 €	.....	.....
<b>TOTAL</b>			.....