



ADHVS42S09/2-24

ADVANTAGE HVS 42S09



- Narrow monocoque body
- Sprung drawbar
- Wheels 620/75R26
- Hydraulic brakes
- Ø 820 mm vertical beaters with Hardox knives
- Guillotine door
- Hydraulic installation

Standard equipment

- Monocoque, monoblock body with lengthwise fold
- Manufactured according to EN 690 standard
- Moving floor with 2 shipping chains (Ø 14 mm 25 t per link except on model 59S16 => Ø 16 mm - 32 t)
- Moving floor drive via tractor hydraulics, manual flow adjustment
- Reversible, interchangeable HARDOX blades (thickness: 8 mm)
- Moulded gearwheels
- Homocinetic P.T.O.-shaft with cam limiter
- Free wheel on the spreading system
- Reversing camera with 7" LCD colour screen
- Anti-projection front cover
- Protected lighting with manual folding on tubes with springs

- LED flash bar connected to lighting
- Galvanised side boards
- Sealing flap at the front and on the spreading table
- Dual-line air brakes
- Sprung drawbar
- Ø 50 mm bolted flat eyelet
- Hydraulic parking stand
- 2 vertical beaters with regular spirals (Ø 820 mm) with removable blades (spiral thickness: 10 mm in ST 420 reinforced steel)
- 1.000 rpm drive shaft beater rotation speed: 420 rpm
- Moving floor with 2 shipping chains (Ø 14 mm 25 T per link)
- Tubular slats of moving floor (70 x 35)

Specific equipment ADHVS42S09/2-24

L-HVS42S09-24 HVS 42S09 muck spreader

KHFR Machine subject to French national certification

3633 Wheels 620/75R26 (ALLIANCE) A360 167 A8 (Ø 1.590 x 625 mm, 5.450 kg per wheel at 40 km/h

and 3,2 bar) instead of 400R22.5

Hydraulic brakes instead of air brakes on single-axle model 315

L932015 Guillotine door from 37S08 to 51S12

Independent industrial hydraulic installation (including hydraulic filter and Ferti-CONTROL 500) 5271

3663 Extra cost for low flow electro-hydraulic functions (only available on muck spreaders and

DRAKKAR) - per function

	Total €	Discount %	NET
RETAIL	42 155 €		
		TOTAL	

V 03-03-2025