

## ADXXL58D22/5-24

## ADVANTAGE GOLD II XXL 58D22



- Tapered body made of HLE420
- Bogie with parabolic leaves
- Air brakes
- Wheels 560/60R22.5
- Hydraulic door with grain chute
- European certification 30 km/h

### Standard equipment

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>✓ Reinforced tapered monocoque body with upper body edge protection and reinforcing lengthwise fold (ST420 high tensile steel - 4 mm)</li> <li>✓ 1-part hydraulic door (with seal and safety system with check valve)</li> <li>✓ 500 x 500 mm multi-position central grain chute (with notches)</li> <li>✓ Sight window on body (with perspex plate and galvanised protective grating)</li> <li>✓ Galvanised access ladder</li> <li>✓ Sprung drawbar</li> <li>✓ Ø 50 mm bolted flat eyelet</li> <li>✓ Hydraulic parking stand</li> <li>✓ Hose holder</li> </ul> | <ul style="list-style-type: none"> <li>✓ Dual-line air brakes</li> <li>✓ Rear bumper</li> <li>✓ LED flash light (flashing beacon on lighting)</li> <li>✓ Bogie with parabolic leaves (1,480 mm on 53D19 and 58D22 and 1,600 mm on 62D24)</li> <li>✓ Tubular chassis:                     <ul style="list-style-type: none"> <li>- 300 x 100 x 8 mm on 5300D,</li> <li>- 300 x 100 x 10 mm on 5800D and 6200D.</li> </ul> </li> <li>✓ Tipping system with direct connection to the tractor</li> <li>✓ Pre-equipment for weight transfer</li> </ul> |
|--|---|

### Specific equipment ADXXL58D22/5-24

- L-XXL2-58D22-24 GOLD2 XXL 5800D monocoque tipping trailer
- **KHEU30-16** European certification for 15,5 T maximum permissible weight on the axles (+ 3 T on the eyelet) at 30 km/h for double-axle vehicle (cat. R)
- **2212 x 2** Wheels 560/60R22.5 (BKT) Flotation 630 Ultra 161 D (Ø 1.244 x 543 mm, 6.300 kg per wheel at 40 km/h and 4 bar) instead of 400R22.5
- **3153** Air brakes with spring-brake actuator instead of standard parking brake (air brakes compulsory)
- **1526** LED side marker lights

	Total €	Discount %	NET
<b>RETAIL</b>	39.315 €	.....	.....
<b>TOTAL</b>			.....