

ADGO46S13/1-22

ADVANTAGE GOLIATH 46S13



- Narrow monocoque body
- Sprung drawbar
- Wheels 620/75R26
- Hydraulic brakes
- Ø 900 mm vertical beaters with Hardox knives
- Retractable hammers on wear rings
- Hydraulic tensioning of the moving floor
- Guillotine door

Standard equipment

- | | |
|---|---|
| ✓ Monocoque body with monoblock rounded side walls | ✓ Anti-projection front cover |
| ✓ 2 vertical beaters with removable coupling and regular spirals (Ø 900 mm) with removable blades on wear rings (spiral thickness: 10 mm) | ✓ Protected lights folding automatically with moving floor drive |
| ✓ Reversible and interchangeable HARDOX blades (10 mm thick) | ✓ Galvanized side boards |
| ✓ 1.000 rpm drive shaft - beater rotation speed: 430 rpm | ✓ Sealing flap at the front and on the spreading table |
| ✓ Bolted rectangular slats of moving floor (80 x 40) | ✓ LED flash bar connected on lighting |
| ✓ Hydraulic tensioning of the moving floor with under-tension security and RE mode locking | ✓ Ladder (EN 690) |
| ✓ Moving floor drive by tractor hydraulics with proportional electric control at the flow regulator (LB300 control box - max. 2 functions on the control box) | ✓ Removable mudguard |
| ✓ Reinforced reduction gearbox for single-speed moving floor | ✓ Hydraulic brakes |
| ✓ Mechanically welded steel gearwheels | ✓ Sprung drawbar |
| ✓ Protected P.T.O. and drive shaft | ✓ Hydraulic stand |
| ✓ Homocinetic transmission (cam security) | ✓ Certification 2020 |
| ✓ Free wheel on the spreading system | ✓ Moving floor with 2 shipping chains (Ø 14 mm links - 25 t per link) |

Specific equipment ADGO46S13/1-22

- **L-GO46S13** GOLIATH 46S13 muck spreader
- **3633** Wheels 620/75R26 (ALLIANCE) A360 167 A8 (Ø 1.590 x 625 mm, 5.450 kg per wheel at 40 km/h and 3,2 bar) instead of 400R22.5
- **L932175** Guillotine door for 46S13 and 54S15
- **L955033** Beater with spoon knives (1 knife on 2) instead of standard beater

	Total €	Discount %	NET
RETAIL	50.335 €
TOTAL		