



## ADXXL62D24/5-24

## **ADVANTAGE GOLD II XXL 62D2**



- Tapered body in HLE 420
- Bogie with parabolic leaves and rear free-steering axle
- Air brakes
- Wheels 600/55R26.5
- · Hydraulic door with grain chute
- European certification 40 km/h

## Standard equipment

- Reinforced tapered monocoque body with upper body edge protection and reinforcing lengthwise fold (ST420 high tensile steel -4 mm)
- √ Chassis made of 300 x 100 x 10 mm tubes
- √ 1-part hydraulic door (with seal and safety system with check valve)
- √ 500 x 500 mm multi-position central grain chute (with notches)
- Sight window on body (with perspex plate and galvanised protective grating)
- √ Galvanised access ladder
- √ Sprung drawbar
- √ Ø 50 mm bolted flat eyelet
- √ Hydraulic parking stand
- √ Hose holder

- √ Dual-line air brakes
- / Rear bumper
- √ LED flash light (flashing beacon on lighting)
- √ Bogie with parabolic leaves
- √ Tubular chassis:
  - 300 x 100 x 8 mm on 53D19,
  - 300 x 100 x 10 mm on 58D22 and 62D24.
- √ Tipping system with direct connection to the tractor
- / Pre-equipment for weight transfer

## Specific equipment ADXXL62D24/5-24

GOLD2 XXL 62D24 monocoque tipping trailer

• KHEU40-18 European certification for 18 T maximum permissible weight on the axles (+ 3 / 4 T on the eyelet)

at 40 km/h for double-axle vehicle (cat. R)

• 074 Free steering axle with shock absorber(s) and hydraulic locking system (DA). WARNING: the free

steering axle must be locked as soon as you reach 15 km/h.

• 3785 x 2 Wheels 600/55R26.5 (BKT) FL630 Super 165 D (Ø 1.333 x 611 mm, 7.005 kg per wheel at 40

km/h and 4 bar) instead of 400R22.5

• 3153 Air brakes with spring-brake actuator instead of standard parking brake (air brakes compulsory)

138 Braking power in proportion to the load on bogie or rocker beam with sprung drawbar (air brakes

compulsory)

1526 LED side marker lights

	Total €	Discount %	NET
RETAIL	49 769 €		
		TOTAL	

V 09-04-2025