

## ADGO62S19/1-24

## ADVANTAGE GOLIATH 62S19



- Narrow monocoque body
- Sprung drawbar
- Wheels 650/75R32
- Hydraulic brakes
- Ø 900 mm vertical beaters with Hardox knives
- Guillotine door
- Hydraulic installation
- DPA (proportional flow) on Ferti-CONTROL 4000 control box

### Standard equipment

- |                                                                                                                                               |                                                                       |
|-----------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|
| ✓ Monocoque body with monoblock rounded side walls                                                                                            | ✓ Free wheel on the spreading system                                  |
| ✓ Manufactured according to EN 690 standard                                                                                                   | ✓ Reversing camera with 7" LCD colour screen                          |
| ✓ 2 vertical beaters with removable coupling and balanced spirals (Ø 900 mm) with retractable hammers on wear rings (spiral thickness: 10 mm) | ✓ Anti-projection front cover                                         |
| ✓ Reversible, interchangeable HARDOX blades (thickness: 10 mm)                                                                                | ✓ Galvanised side boards                                              |
| ✓ 1,000-rpm drive shaft - beater rotation speed: 430 rpm                                                                                      | ✓ Sealing flap at the front and on the spreading table                |
| ✓ Bolted rectangular moving floor slats (80 x 40 mm)                                                                                          | ✓ LED flash bar connected to lighting                                 |
| ✓ Hydraulic tensioning of the moving floor with under-tension security and RE mode locking                                                    | ✓ Removable mudguards                                                 |
| ✓ Moving floor drive via tractor hydraulics, manual flow adjustment                                                                           | ✓ Dual-line air brakes                                                |
| ✓ Reinforced single-speed reduction gearbox of moving floor                                                                                   | ✓ Sprung drawbar                                                      |
| ✓ Mechanically welded steel gearwheels                                                                                                        | ✓ Ø 50 mm bolted flat eyelet                                          |
| ✓ Protected P.T.O. and drive shaft                                                                                                            | ✓ Hydraulic parking stand                                             |
| ✓ Homocinetic transmission (cam security)                                                                                                     | ✓ Moving floor with 2 shipping chains (Ø 16 mm links - 32 t per link) |

### Specific equipment ADGO62S19/1-24

- L-GO62S19-24 GOLIATH 62S19 muck spreader
- **3508** Wheels 650/75R32 (MITAS) AC70G 172 A8 (Ø 1,795 x 650 mm, 3,245 kg per wheel at 40 km/h and 0.6 bar and 11,365 kg per wheel at 40 km/h and 4 bar) instead of 400R22.5
- **315** Hydraulic brakes instead of air brakes on single-axle model
- **L932176** Guillotine door for 54S17 and 62S19
- **5784** Beaters with spoon knives (1 knife on 2) instead of standard beaters
- **5785** Revolution counter for the moving floor shaft
- **3666** Independent industrial hydraulic installation (including hydraulic filter and Ferti-CONTROL 4000)
- **3732** DPA on Ferti-CONTROL 4000 allowing the regulation of the floor speed according to the driving speed - including display of the driving speed (M/min). Allows also the regulation of the speed of the floor depending on the door opening (in combination with ref. 3116 to be taken additionally).  
WARNING:  
- on HORIZON model: ref. 3116 compulsory;  
- Ferti-CONTROL 4000 compulsory.
- **3116** Electronic door opening indicator, spreader counter and moving floor starting safety (according to the door opening) - guillotine door compulsory)
- **3663** Extra cost for low flow electro-hydraulic functions (only available on muck spreaders and DRAKKAR) - per function

|        | Total €  | Discount % | NET   |
|--------|----------|------------|-------|
| RETAIL | 69 490 € | .....      | ..... |
| TOTAL  |          |            | ..... |