

**leboulch**



[www.leboulch.com](http://www.leboulch.com)

# GOLD<sub>2</sub>

**THE TIPPING TRAILER THAT IS  
WORTH ITS WEIGHT IN GOLD!**




**A complete machine with many equipment options possible**

# leboulch

## STANDARD EQUIPMENT



**Folding aluminium ladder, galvanised side mudguards and predispositions for optional equipment** (side bumper and thermoplastic mudguards).




**Tapered body** (2.25 m at the front and 2.3 m at the rear), wider at the bottom than at the top to facilitate unloading.



**Document tube** with individualised parts book and user manual.

**Sturdy 300 x 100 x 10 mm tubular chassis stringer** for the entire range, except for 4700S, 5300S and 5300D (300 x 100 x 8 mm).



**Choice of eyelets**

- (A) Bolted Ø 50 mm (standard)
- (B) Bolted knee-joint (option)




**Hydraulic folding parking stand** attached directly to the trailer chassis to free the drawbar and facilitate turning.




**Noise-reducing silentblock** for centering and lateral locking of the body on the chassis.







**High-clearance rear door with hydraulic opening** for easy unloading of silage with extensions and to avoid scraping the pile when tipping at the highest.




**Door opening cylinders** protected by the door arms and upper body edge strip.

**Double door-closing safety system:** hydraulic with check valve and mechanical with 2 adjustable hooks. Hydraulic pipes protected by the rear post.



**Flexible seal** in a rail along the entire height of the door (watertight without grain chute).



**1 or 2 grain hatch(es)** with pre-equipment for removable chute.



**Bogie suspension with parabolic leaves** (on models from 5300D to 6700D): for improved crossing capacity and load distribution.



**Tandem or tridem suspension with parabolic spring leaves and rods** (on models from 7300D to 8500T) for both road and agricultural use.



**Galvanised rear bumper** with adjustable height and depth.




## GOLD<sup>2</sup> XL

- ✓ Single or double axle
- ✓ 16 to 24 tons
- ✓ Sturdy and reliable


## GOLD<sup>2</sup> XXL

- ✓ Double or triple axle
- ✓ 19 to 32 tons
- ✓ High resistance to intensive use


XL 4700S




XXL 5300D



XXL 6200D




XL 5300S




XXL 5800D



XXL 6700D




XL 5300D




XXL 7300D




XL 5800D




XXL 7900T



XL 6200D



XXL 8500T



## OPTIONS

**300 mm** (steel or aluminium), **500 mm** (aluminium) or **700 mm** (aluminium) extensions, stackable up to 1 m.  
2-part side extensions on single- and double-axle models, and 3-part extensions on triple-axle models.




300




500



700



300 + 500



300 + 700

### Rolling cover

